

6491X H07V-R Cable 450/750V

Plain annealed stranded copper conductor, PVC insulated, 450/750 volts grade to BS EN 50525-2-31

Lighting (where applicable) ~~EN 50281-3~~
 Class 2 stranded circular or circular compacted
 Maximum 70 °C Minimum bending 0°C
 Diameter up to 10mm

Applications:

4 x overall diameter
 5 x overall diameter

For current rating information, refer to Table 4D1A

Size sq mm		Max diameter over	RT of	Nominal overall	Weight
	2	1.59	0.7	3.0	
	2	2.01	0.8	3.7	
	2	2.55	0.8	4.2	
	2	3.12	0.8	4.8	
	2	4.05	1.0	6.1	
	2	5.10	1.0	7.1	
	2	6.42	1.2	8.9	
	2	7.65	1.2	10.1	
	2	8.90	1.4	11.8	
	2	10.70	1.4	13.6	
	2	12.60	1.6	15.9	
	2	14.21	1.6	17.5	
	2	15.75	1.8	19.4	
	2	17.64	2.0	21.7	
	2	20.25	2.2	24.5	
	2	22.68	2.4	27.5	
	2	25.65	2.6	30.9	
	2	28.80	2.8	34.5	
	2	32.76	2.8	38.4	6210

